



TECHNICAL DATA SHEET EXOTIC 201

WoodPlus Coatings Group Ltd.
12-1064 Salk Rd., Suite 233
Pickering, Ontario, Canada L1W 4B5
Bus.: 1-844-373-9663



DESCRIPTION

WoodPlus™ Exotic 201 is a water reducible blend of natural oils and special UV blockers that provides excellent protection of **NEW WOOD** (not for use on pressure treated wood) from any weather condition. **Exotic 201** does not contain any solvents (Zero VOC). **Exotic 201** provides a natural look to new wood surfaces.

RECOMMENDED USES

Exotic 201 is designed for use on decks and patios only. **Exotic 201** is specially formulated to protect deck surfaces built with **NEW WOOD ONLY** such as exotic wood (ipe, mahogany, teak, etc.), torrefied wood as well as cedar and other soft wood species. Exotic 201 neutral base can be used on its own or be tinted with universal colorants.

IMPORTANT: APPLY ONE COAT ONLY. REAPPLY ONE COAT YEARLY OR AS NEEDED. DO NOT USE ON PRESSURE TREATED WOOD.

PRODUCT CHARACTERISTICS

- Designed for high performance in any climate
- Outstanding UV protection
- Self priming
- Excellent water repellency
- Excellent physical wear characteristics
- Excellent colour retention
- Easy maintenance – soap and water cleanup
- Excellent deep penetration properties.

TECHNICAL DATA

Colour:	Coloured liquid	Flashpoint:	95°C
Odour:	Slight natural oil	VOC content:	Zero
Solids:	20+/- 1% by weight	Gloss level:	10 G.U.
Weight/gal:	10.48 lb/gal	Viscosity:	250 cpu

SURFACE PREPARATION INSTRUCTIONS

- Wood must be clean and dry.
- Remove all dirt dust, wax, grease, mildew and mill glaze.
- All wood should be dry and free of moisture (less than 19% moisture content).
- New smooth wood must be sanded with 60-80 grit sandpaper to remove mill glaze.
- Remove all sanding dust with acetone prior to application.

APPLICATION INSTRUCTIONS (For more information, please scan the QR further below or go to:

www.woodpluscoatings.com .)

- Product is ready to use. Do not thin.
- Stir thoroughly before and during use.
- APPLY ONE COAT ONLY.
- DO NOT apply in direct sunlight or on a surface that is hot to the touch.
- Temperature must be above 10°C and not more than 30°C.
- Apply in the direction of the grain completing a full board at a time.
- Maintain a wet edge and saturate any open or cut end boards.
- DO NOT apply in wet weather or when inclement weather is imminent.



TECHNICAL DATA SHEET EXOTIC 201

WoodPlus Coatings Group Ltd.
12-1064 Salk Rd., Suite 233
Pickering, Ontario, Canada L1W 4B5
Bus.: 1-844-373-9663



COVERAGE

500-600^{ft}²/gal (50-60m²/3.78L)

Note: The above coverage is approximate and may vary due to surface porosity of the substrate.

CLEANUP

Use soap and water.

CAUTION: OIL SOAKED CLOTHING / RAGS SHOULD BE IMMERSSED IN WATER IMMEDIATELY TO PREVENT SPONTANEOUS COMBUSTION.

DRY TIME

Will vary according to temperature, humidity levels and exposure to sunlight. Areas with high air flow will dry quicker than those with low or no air flow.

AVAILABLE CONTAINER SIZES

Gallons. Other sizes available upon request.

MAINTENANCE

Keep the deck surface clean by periodic washing with water and a soft brush to remove dirt and airborne pollutants. Re-apply Exotic 201 yearly or as needed. Before applying a maintenance coat, clean with TSP and rinse thoroughly. Wait 24 hours for surface to dry.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

© ALL RIGHTS RESERVED